LUMINA

Porcelain Tile | Technical Data Sheet

PRODUCT

Material	Glazed porcelain tile, rectified edge
Look	Onyx look, modern
Finish	Matte and Polished
Thickness	3/8" (9 mm)
Use	Interior floors and walls. Polished: dry areas recommended.
Colors	White, Jade, Azzurro (matte); Bianco, Jade, Azzurro (polished)
Shade variation	V4 (high); 16 different faces
Origin	Italy

COLORS, SIZES AND PACKAGING

Product	Size	Pcs/box	Sq ft/box	Weight/box*
Lumina matte (3 colors)	24" x 48"	2	15.5	60.5 lb
Lumina polished (3 colors)	24" x 48"	2	15.5	60.5 lb

* Approximate weight. Pieces per box are calculated from the coverage per box.

PERFORMANCE

Durability	Porcelain: resistant to stains, scratches and household chemicals.
Water	Water absorption below 0.1%. PEI class 5 (matte), class 4 (polished).
Slip resistance	Polished surfaces are slippery when wet (DCOF below 0.42): use in dry areas.
Care	Clean with water and a pH-neutral cleaner. No sealing required on the glazed surface.

SLIP RESISTANCE STANDARDS (REFERENCE)

DIN EN 16165:2021 Annex B (ex DIN 51130), shod foot on oiled ramp: R9 (6-10 deg), R10 (10-19), R11 (19-27), R12 (27-35), R13 (>35). DCOF ANSI A326.3 (USA, wet): interior dry >=0.42, interior wet >=0.42, interior wet plus >=0.50, exterior wet >=0.55.

Packaging, colors and sizes are subject to normal variation; information is believed accurate but is not legally binding.

LUMINA

Porcelanato | Ficha Tecnica

PRODUCTO

Material	Porcelanato esmaltado, borde rectificado
Aspecto	Efecto onix, moderno
Acabado	Mate y Pulido
Espesor	3/8" (9 mm)
Uso	Pisos y paredes interiores. Pulido: recomendado para zonas secas.
Colores	White, Jade, Azzurro (mate); Bianco, Jade, Azzurro (pulido)
Variacion de tono	V4 (alta); 16 caras distintas
Origen	Italia

COLORES, FORMATOS Y EMPAQUE

Producto	Medida	Pzas/caja	Sq ft/caja	Peso/caja*
Lumina matte (3 colors)	24" x 48"	2	15.5	60.5 lb
Lumina polished (3 colors)	24" x 48"	2	15.5	60.5 lb

* Peso aproximado. Las piezas por caja se calculan a partir de la cobertura por caja.

DESEMPENO

Durabilidad	Porcelanato: resistente a manchas, rayones y quimicos domesticos.
Agua	Absorcion de agua menor a 0.1%. PEI clase 5 (mate), clase 4 (pulido).
Antideslizante	Las superficies pulidas resbalan en mojado (DCOF menor a 0.42): usar en zonas secas.
Cuidado	Limpiar con agua y limpiador de pH neutro. No requiere sellado en la superficie esmaltada.

NORMAS DE DESLIZAMIENTO (REFERENCIA)

DIN EN 16165:2021 Anexo B (ex DIN 51130), calzado en rampa con aceite: R9 (6-10 grados), R10 (10-19), R11 (19-27), R12 (27-35), R13 (>35). DCOF ANSI A326.3 (EE. UU., mojado): interior seco >=0.42, interior mojado >=0.42, interior mojado plus >=0.50, exterior mojado >=0.55.

Empaque, colores y medidas sujetos a variacion normal; informacion precisa a nuestro mejor saber, no legalmente vinculante.