


## Suggested Applications




## Installation Suggestions



## Porcelain Type

☐ through-body ☒ color-bodied ☒ glazed ☐ unglazed ☐ double-loaded ☐ other \_\_\_\_\_

## Shade Variation



## Slip Resistance

ASTM C-1028  
ANSI A137.1  
DIN 51097/51130

DCOF	Values	Applications
<input checked="" type="checkbox"/> 0.63	0.42	Recommended Standard DCOF value for wet/dry commercial flooring
	0.65	Recommended Standard DCOF value for ADA ramps

DIN 51130 \*R9: Industry Standard/ADA Requirements \*\*R11: Recommended For Exterior

<input checked="" type="checkbox"/> R9* (3-10")	<input type="checkbox"/> R10 (10-19")	<input type="checkbox"/> R11** (19-27")
<input type="checkbox"/> R12 (27-35")	<input type="checkbox"/> R13 (>35")	

DIN 51097

Class	Typical Applications	Critical Angle
<input type="checkbox"/> A	Barefoot, but mainly dry aisles and walkways, dry changing areas	≥12°
<input type="checkbox"/> B	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)	≥18°
<input type="checkbox"/> C	Areas constantly under water, e.g. steps into pools, foot baths, included pool surrounds, jacuzzis (plus all Class A&B areas)	≥24°

## Scratch Resistance

MOH'S SCALE  
UNI EN ISO  
10545.6

MINERAL	
1. Talc (Talc)	6. Microline (Glass, Glazed Tile)
2. Gypsum (Fingernail)	7. Quartz (Unglazed Porcelain)
3. Calcite (Penny)	8. Topaz (Granite)
4. Fluorite (Some Marbles)	9. Corundum (Ruby)
5. Apatite (Knife Blade)	10. Diamond (Diamond)

Industry standard ≤175mm<sup>2</sup>

## Wear Resistance

PEI RATING  
UNI EN ISO  
10545.7

- ☐ Class 1: Walls only
  - ☐ Class 2: Residential floors w/minimal abrasive traffic
  - ☐ Class 3: Residential interiors/light commercial traffic
  - ☐ Class 4: Medium commercial applications
  - ☒ Class 5: All commercial applications/heavy traffic
- \*Wear can vary greatly. please consult with a professional.*

## Stain Resistance

ASTM C1378-04  
UNI EN ISO  
10545.14

- 5: Removed after 5 minutes (hot water running)
- 4: Removed by manual cleaning (weak detergent)
- 3: Removed by mechanical cleaning (strong detergent)
- 2: Removed by immersion (24 hrs in suitable solvent)
- 1: Stain not removed

## Water Absorption

ASTM C-373  
UNI EN ISO  
10545.3

<input checked="" type="checkbox"/> Absorbs 0-.5%	<input type="checkbox"/> Absorbs .5-3%	<input type="checkbox"/> Absorbs 3-7%	<input type="checkbox"/> Absorbs 7% +
Impervious Interior/Exterior Frost Resistant	Vitreous Interior/Exterior Frost Resistant	Semi-Vitreous Indoor Use Only	Non-Vitreous Indoor Use Only

## Breaking Strength

ASTM C648  
UNI EN ISO  
10545.4



## Facial Dimension

ASTM C499-09  
UNI EN ISO  
10545.02

	Standard	Tolerance	Result
flatness	± 5mm	± .5%	PASS
thickness	± 6mm	± .5%	PASS
straightness	± 4.5mm	± .5%	PASS
squareness	± 5.4mm	± .6%	PASS
sides L/W	± 1.1mm ± 4.5mm	± .5%	PASS

## Chemical Resistance

ASTM C650  
UNI EN ISO  
10545.13

Allowances for:	result
Acid	PASS
Bases	PASS
Chemicals	PASS

## Leed Information



REQUIREMENTS  
FOR COMMERCIAL  
INTERIORS/NEW  
CONSTRUCTION

Sustainable Sites	1 Point	Materials & Resources	1 Point	2 Points
Site selection		M&R CREDIT 2		
SS CREDIT 1		Construction Waste Management: Recycling salvaged construction waste in to new reusable materials.	50% <input type="checkbox"/>	70% <input checked="" type="checkbox"/>
Heat Island Effect-non roof				
Material with a solar reflectant index of at least 29.				
Energy & Atmosphere	1 Point	M&R CREDIT 4.1-4.2		
EA CREDIT 4		Recycled Content: The sum of post consumer plus 1/2 of the pre consumer reps at least 10-20% of total value of materials.	10% <input type="checkbox"/>	20% <input checked="" type="checkbox"/>
Green Power: Products that optimize energy performance for floors and walls using thermal conductivity. BTU-FT				
Indoor Environmental Quality	1 Point	M&R CREDIT 5		
Low-Emitting Materials-Flooring Systems		Regional Materials: Materials manufactured within 500 miles of the project site.	10% <input type="checkbox"/>	20% <input type="checkbox"/>
IEQ CREDIT 3.1-7				
Green Cleaning: Reducing occupants exposure to hazardous cleaning chemicals.	<input type="checkbox"/>			
IEQ CREDIT 4.1		Innovation in Design		1-5 Points
Low Emitting Adhesives: Products less than 65 G/L VOC	<input type="checkbox"/>	ID CREDIT 1		
IEQ CREDIT 4.3		Innovation in Design		<input checked="" type="checkbox"/>
Low Emitting Materials: Flooring systems.	<input checked="" type="checkbox"/>	Measurable exemplary environmental performance.		