



- TERRACOTTA
- QUARRY TILES
- CONCRETE
- UNPOLISHED NATURAL STONE
- TUFO



WHAT IT'S FOR

- Stain-proofing agent for internal and external surfaces.
- Protective base coat before waxing internal surfaces with rustic or textured finishes.
- Excellent for coloured cement tiles.
- Natural effect breathing protection.

ADVANTAGES

- Does not alter original colour and appearance.
- Does not form surface film.
- Does not alter terracotta frost resistance.
- The product is certified foodsafe.
- Excellent on rustic ground terracotta and tumbled marble.
- Ideal for use near kitchens, barbecues and car driveways.

HOW TO USE IT

No dilution required: ready to use.

Application:

For exterior use: Apply one coat of water-repellent product beforehand (FILAES82 if it is a terracotta surface or HYDROREP on a natural stone surface) with the surface dry and clean. Allow until it is absolutely dry (about 24 hours), then apply FILAFOB undiluted using a large, flat paintbrush, also soaking the joints well. Allow 24 hours before walking on the floor.

For interior use: With the surface clean and dry, apply FILAFOB undiluted using a large, flat paintbrush, also soaking the joints well. Wait 24 hours before walking on the floor. Complete the treatment with the most suitable wax for the specific surface (e.g. FILAMATT - natural effect, FILASATIN - satin effect, FILALONGLIFE - polished effect).

Maintenance: diluted solution of FILACLEANER.

Caution:

Never apply FILAFOB onto a surface that is already waxed. Do not apply FILAFOB during the hottest hours of the day in summer. Carry out a patch test on a small surface area to check for any changes in colour. Do not apply the product externally if rain is forecast.

COVERAGE

With one litre:

Stone	10/20 m ²
Terracotta rustic Tuscan, polished	15/20 m ²
Terracotta handmade, Spanish, hollow tile, brick	5/10 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

250-ml bottles in boxes of 12.
1-litre cans in boxes of 6.
5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Ventilate the area if applied on internal surfaces.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.
- Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.
- Does not protect marble and limestone from acid.

TEMPERATURES

Storage temperature: from 0° to 30°C
The product should be applied to materials with temperature between 5° and 30° C.

COMPOSITION

A blend of synthetic resins dispersed in de-aromatised hydrocarbon solvent. Pursuant to it Leg Dec. No.161/06
Binding primers (waterproofing). EU limit value for this product (Cat: 1/h): 750 g/l (2010). This product contains no more than 57.99 g/l.

LABELLING

Warning: Danger

Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause long lasting harmful effects to aquatic life. Repeated exposure may cause skin dryness or cracking.

Caution recommendations:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations. Contains: ISOALCANI C10-C12.



TECHNICAL FEATURES

Appearance: liquid

Colour: transparent colourless

Odour: typical hydrocarbon solvent smell

Density: 0.763 kg/l

Flash point: 40 °C

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.



Fila Chemicals USA

Revision nr. 3

Dated 30/3/2015

FILAFOB

Printed on 30/03/2015

Page n. 1/13

Safety data sheet according to U.S.A. Federal Hazcom 2012

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

FILAFOB

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

Stain repellent for natural stone, concrete and terracotta

1.3. Details of the supplier of the safety data sheet

Name

Fila Chemicals USA

Full address

10800 NW 21st St Ste # 170

District and Country

Miami, FL 33172

Tel. (305) 513-0708

Fax. (305) 513-0728

filausa@filasolutions.com

e-mail address of the competent person

responsible for the Safety Data Sheet

sds@filasolutions.com

1.4. Emergency telephone number

For urgent inquiries refer to

800-424-9300 CHEMTREC

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Flammable liquid, category 3

Aspiration hazard, category 1

Specific target organ toxicity - single exposure, category 3

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.


May cause drowsiness or dizziness

Hazard pictograms:



Signal words:

Danger

	Fila Chemicals USA	Revision nr. 3
	FILAFOB	Dated 30/3/2015 Printed on 30/03/2015 Page n. 2/13

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness

Precautionary statements:

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground / bond container and receiving equipment.
P241	Use explosion-proof electrical / ventilating / lighting / . . . / equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection / face protection.

Response:

P303+P361+P353	IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
P331	DO NOT induce vomiting.
P370+P378	In case of fire: use dry chemical or carbon dioxide (CO2) to extinguish.

Storage:

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal:

P501	Dispose of contents / container in accordance with local/national regulations.
-------------	--

2.2. Other hazards.

Additional hazards. Repeated exposure may cause skin dryness or cracking

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.


3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification:	Trade Secret:
NAPHTA (PETROL.) HYDROTREATED HEAVY			
CAS. 64742-48-9	90 - 95	* Flammable liquid, category 3 H226, Aspiration hazard, category 1 H304, Specific target organ toxicity - single exposure, category 3 H336	§
DIPROPYLENE GLYCOL MONOMETHYL ETHER			
CAS. - 34590-94-8	5 - 9	Flammable liquid, category 4 H227	§

* The classification as a carcinogen or mutagen need not apply because the substance contains less than 0,1 % w/w benzene.

§ The exact percentage (concentration) of composition has been withheld as a trade secret.

	Fila Chemicals USA	Revision nr. 3
	FILAFOB	Dated 30/3/2015 Printed on 30/03/2015 Page n. 3/13

Note: Upper limit is not included into the range.

The full wording of the hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.



8.1. Control parameters.

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU TLV-ACGIH	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. ACGIH 2014

NAPHTA (PETROL.) HYDROTREATED HEAVY

Threshold Limit Value.						
Type	Country	TWA/8h		STEL/15min		Other Exposure Manufacturer recommends
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	-	-	-	-	TWA of 1200 mg/m3 197 ppm

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Threshold Limit Value.						
Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	606	100	909	150	SKIN.
OEL	EU	308	50			SKIN.
OSHA	USA	600	100			SKIN.
CAL/OSHA	USA	600	100	900	150	SKIN.
NIOSH	USA	600	100	900	150	SKIN.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.



Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	Transparent, colorless liquid.
Odour	Solvent odor
Odour threshold.	Not available.
pH.	N. A.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	107.6°F (42°C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,764 Kg/l
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Solid content: 2.41%
VOC (volatile carbon) : 97.6 %

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

**FILAFOB**

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.**11.1. Information on toxicological effects.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

NAPHTA (PETROL.) HYDROTREATED HEAVY

LD50 (Oral).> 5000 mg/kg Rat

LD50 (Dermal).> 2000 mg/kg Rabbit

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, and OSHA.

SECTION 12. Ecological information.

This product may damage the structure and/or the functions of the aquatic ecosystems in the long and/or delayed term.

12.1. Toxicity.

NAPHTA (PETROL.)

HYDROTREATED HEAVY

LC50 - for Fish.

> 1000 mg/l/96h Oncorhynchus mykiss

EC50 - for Algae / Aquatic
Plants.

> 1000 mg/l/48h Daphnia magna



EC50 - for Algae / Aquatic
Plants.

> 1000 mg/l/72h *Pseudokirchneriella subcapitata*

12.2. Persistence and degradability.

DIPROPYLENE
GLYCOL
MONOMETHYL
ETHER

Solubility in water.

mg/l 1000 - 10000

Rapidly biodegradable.

NAPHTA (PETROL.)
HYDROTREATED HEAVY

Rapidly biodegradable

12.3. Bioaccumulative potential.

DIPROPYLENE
GLYCOL
MONOMETHYL
ETHER

Partition coefficient: n-
octanol/water.

0,0043

12.4. Mobility in soil.

Highly volatile, will partition rapidly to air. Not expected to partition to sediment and suspended solids in wastewater.

NAPHTA (PETROL.)
HYDROTREATED HEAVY

Partition coefficient:
soil/water.

1.78

12.5. Results of PBT and vPvB assessment.


On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

	Fila Chemicals USA	Revision nr. 3
	FILAFOB	Dated 30/3/2015 Printed on 30/03/2015 Page n. 9/13

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

These goods must be transported by vehicles authorized to transport hazardous materials according to the provisions set out in the current regulations of the U.S. DOT, Canadian TDG, the IMDG and IATA.

Rail and Truck Shipments

DOT Shipping Name: HYDROCARBONS, LIQUIDS, N.O.S. (Naphtha (petroleum), hydrotreated heavy)

DOT ID Number UN 3295

DOT Hazard Class & Packing Group 3 (Flammable liquid), III

DOT Shipping Label Flammable

TDG Shipping Name: HYDROCARBONS, LIQUIDS, N.O.S. (Naphtha (petroleum), hydrotreated heavy)

TDG ID Number UN 3295

TDG DOT Hazard Class & Packing Group 3 (Flammable liquid), III

TDG Shipping Label Flammable

Water Shipments

IMO Shipping Name: HYDROCARBONS, LIQUIDS, N.O.S. (Naphtha (petroleum), hydrotreated heavy)

IMO ID Number UN 3295

IMO DOT Hazard Class & Packing Group 3 (Flammable liquid), III

IMO Shipping Label 3 (Flammable)

IMO EMS F-E, S-D

Air Shipments

IATA Shipping Name: HYDROCARBONS, LIQUIDS, N.O.S. (Naphtha (petroleum), hydrotreated heavy)

IATA ID Number UN 3295

IATA DOT Hazard Class & Packing Group 3 (Flammable liquid), III

IATA Shipping Label 3 (Flammable)

IATA Packing Instructions Cargo: 310 Maximum quantity: 220 L
Passenger: 309 Maximum quantity: 60 L

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

TSCA Inventory Status All ingredients are listed on the TSCA Inventory

Clean Air Act Section 112(b):

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

**FILAFOB**Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act –
Priority Pollutants:

No component(s) listed.

Clean Water Act –
Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

RCRA Code:

No component(s) listed.

**FILAFOB**

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations.

Massachusetts:

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

Minnesota:

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

New Jersey:

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

New York:

No component(s) listed.

Pennsylvania:

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

California:

34590-94-8

DIPROPYLENE GLYCOL
MONOMETHYL ETHER (Glycol
ethers)

Proposition 65:

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Canadian WHMIS.

Information not available.

**SECTION 16. Other information.**

Current Issue Date 03-30-2015
Previous Issue Date 12-30-2010
Previous rev. number 2
Changes in current issue Revision according to Federal Hazcom 2012.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Flam. Liq. 4 Flammable liquid, category 4
Asp. Tox. 1 Aspiration hazard, category 1
STOT SE 3 Specific target organ toxicity - single exposure, category 3
H226 Flammable liquid and vapour.
H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 © RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112©)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition



- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.



1351-15

Date: 05 – May - 2018

LIMITED WARRANTY FOR FILA FOB

Under the terms and conditions set forth in this warranty, Fila Chemicals USA, Corp. (the "**Warrantor**"), whose address is 10800 NW 21st Street, #170 Miami, FL 33172 USA, warrants that Fila FOB (the "**Product**") is free from defects in workmanship and materials, in accordance with UNI EN ISO 9001:2015 and ISO 14001:2015, and that the Product will protect against stains water and oil origin the porous unpolished natural stone surfaces (marble, granite, limestone, sandstone, engineering stone, agglomerate), engineered quartz, concrete, terracotta and quarry tile surfaces, internal and external floors (the "**Surface**") under normal conditions and if used following the Instructions (as hereinafter defined). Fila FOB does not protect marble and limestone from acid.

This warranty extends solely to the original purchaser of the Product (the "**Consumer**") and cannot be transferred to any other party.

The Warrantor warrants that the Surface treated with the Product is protective under normal conditions, provided that: i) the Surface is treated with the Product by diligently following the instructions provided in the Product technical data sheet, as well as in the Warrantor's catalogue, both available on Warrantor's website (www.filasolutions.com) (the "**Instructions**"); and ii) the Surface is maintained weekly with a diluted solution of FILA CLEANER (1:200) and monthly with a diluted solution of FILAPS87 (1:20); iii) when the Product is used under normal and proper circumstances, following correct maintenance instructions with FILA cleaners and repeating the product application every one to three years, depending on the use of the surface, the Product will not deteriorate nor degrade during their **lifetime**.

The term of this warranty begins on the date of purchase of the product and continues for: i) a period of 8 (eight) years if the Surface consists of internal floors; and ii) for a period of 1 (one) year if the Surface consists of external floors.

In the event of a defect, malfunction, or other failure of the Product not caused by any misuse or damage to the Product while in the Consumer's possession, the Warrantor will remedy the failure or defect, without charge to the Consumer, within a reasonable time from Notice (as defined below). The Warrantor can choose either to:



- i) replace the Product; or
- ii) refund the purchase price of the Product to the Consumer.

EXCLUSIONS AND LIMITATIONS

This warranty does not cover damage to the Surface caused by misuse of the Product, abuse of the Product, or accident connected to the usage of the Product, such as:

1. Improper installation of the Product on the Surface;
2. Improper maintenance of the Surface due to the usage of strong acidic cleaners and strong alkaline cleaners;
3. Improper maintenance of the Surface due to the usage of abrasive grinding method to clean;
4. Ordinary wear and tear of the Surface;
5. Damage caused by grout related issues, including but not limited to staining, color variation, discoloration, cracking, chalking, mildew or mold;
6. Usage of any item which might be expected to damage the Surface;
7. Failure to follow the Instructions in the application of the Product to the Surface;
8. Damage caused by Acts of God, including but not limited to fire, flood, earthquake, hurricane, tornado or other types of natural disasters, or caused by unforeseeable circumstances;
9. Damage caused by acts of negligence or failure to comply with applicable codes and regulations, as well as with standard industry practices;
10. Any variation of color or shade of the Surface, different markings, holes, pits, inclusions, veining, density and any other element inherent to the natural stone surfaces.

This warranty does not cover: i) labor costs connected to the replacement of the Surface; ii) costs of the materials necessary to replace the Surface; and iii) any other expenses borne in connection to such replacement.

THIS CONSTITUTES THE ENTIRE EXPRESS WARRANTY FOR THE PRODUCTS PURCHASED. TO THE EXTENT PERMITTED BY LAW, ANY OTHER WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. ANY IMPLIED WARRANTIES ARISING BY OPERATION OF LAW ARE LIMITED IN DURATION TO THE TERMS OF THIS WARRANTY. WARRANTOR WILL NOT BE LIABLE UNDER ANY CIRCUMSTANCES FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, OR FOR LOST PROFITS OR BUSINESS INTERRUPTION LOSS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. NO IMPLIED WARRANTY CAN BE MODIFIED BY COURSE OF DEALING, COURSE OF PERFORMANCE OR USAGE OF TRADE.

Fila Chemicals USA, Corp.
10800 NW 21st Street, #170
Miami, FL 33172 USA

T +1 (305) 513-0708
F +1 (305) 513-0728
www.filasolutions.com
filausa@filasolutions.com



To obtain performance of any obligation under this warranty, the Consumer must take the following steps: i) give written notice of the defect, malfunction, or other failure to Warrantor within 30 (thirty) days of its discovery ("**Notice**"); ii) provide Warrantor with the purchased left over, unused, Product as well as with the purchase invoice; and iii) give Warrantor the opportunity to inspect the alleged defective Product and Surface.

Failure to take any of the above three steps will cause the claim to be automatically rejected.

This warranty gives specific legal rights to the Consumer, who may also have other rights which vary from State to State.

Francesco Pettenon
CEO

Maria Soranzo
R&D Manager – Technical Department



ULTIMATE POROUS STONE SEALER

FOB

ALL POROUS NATURAL STONE, GROUT, CONCRETE, QUARRY TILE, TERRACOTTA

ADVANCED
SOLVENT
TECHNOLOGY



WHAT IT'S FOR

- Natural look, penetrating sealer that protects all porous natural stone, grout, concrete, quarry tile and terracotta against stains.
- Forms an invisible, protective barrier resistant to moisture and stains while allowing water vapor to escape.
- Suitable for indoor and outdoor surfaces.
- Ideal for the treatment of concrete and quarry tile.
- Perfect for honed marble, limestone and travertine.
- Ideal for use in kitchens, under barbecues, on driveways and in high traffic areas both indoors and outdoors.

ADVANTAGES

- Long lasting protection.
- Does not yellow or discolor over time.
- UV resistant.
- Treated surfaces are safe for food contact.
- Does not alter the frost resistance of terracotta.
- PFOA free: non carcinogenic.

HOW TO USE IT

READY TO USE, no dilution necessary.

Indoor surfaces: On a dry and clean surface, apply an even coat of **FOB** with a paintbrush, lambswool or roller applicator. Before the product dries, about 10 minutes, wipe and rub the surface to allow any excess product to completely penetrate or be removed. Wait 8 hours to apply a second coat if necessary, following the instructions above. The surface may be used for normal foot traffic 8 hours after the final coat. Full cure and maximum sealer protection is achieved in 24 hours.

Outdoor surfaces: On a clean and dry surface, apply two coats of **FOB** with a large paintbrush or roller allowing 8 hours between coats.

Caution: Do not apply **FOB** on a previously waxed surface, strip it first. Do not apply **FOB** during the warmest hours of the day in the summer. Before full application, test the product on a small, inconspicuous area of the surface or loose sample to check for any discoloration. Do not apply **FOB** outdoors if rain is in the forecast. The product does not protect surfaces from acid stains.

Storage temperature: Between 32°F and 86°F (0°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

- ▶ **NATURAL LOOK**
- ▶ **LONG-LASTING PROTECTION**
- ▶ **INTERIOR AND EXTERIOR USE**
- ▶ **WORKING PROPERTIES:**
SURFACE TRAFFIC = 8 HOURS
FULL CURE = 24 HOURS



Coverage:

1 GAL (3.78 L)

All natural stone >

430/861 sq. ft. (40-80 m²)

Concrete, quarry tile, terracotta >

646/861 sq. ft. (60-80 m²)

Grout* > 1,400 sq. ft. (130 m²)

Coverage rates are indicative and per coat.

**Grout coverage varies according to tile size, grout joint width and porosity of the grout.*



Packaging:

1 QT (946 ml) 6 plastic bottles per box

1 GAL (3.78 L) 4 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/07/30 - REV. 02

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings

filasolutions.com