DOLCINO

Technical specifications | Matte porcelain tile, limestone look

Product

Material	Porcelain, rectified (EN 14411 Annex G, group BIa)
Finish	Matte (natural)
Thickness	3/8" (9 mm)
Shade variation	V2 (slight variation)
Frost resistance	Frost resistant
Uses	Indoor floors and walls (structured: indoor walls)
Colors	Black, Dark, Grey, Light, Ivory

Sizes and packaging

Size	Pieces / box	Sq ft / box	Weight
12" x 24"	7	13.65	4.35 lb / sq ft
24" x 24"	4	15.6	4.35 lb / sq ft
24" x 48"	2	15.6	4.6 lb / sq ft
24" x 48" structured	2	15.6	4.6 lb / sq ft
2" x 2" mosaic (12" x 12" sheet)	6 sheets	6	4.0 lb / sheet
3" x 24" bullnose	sold per piece	2 LF / piece	2.3 lb / piece

Slip resistance (natural surface)

Test	Value
DCOF, ANSI A326.3 (AcuTest)	Wet >= 0.42
BCRA, D.M. 236 14/06/89	Dry > 0.4 | Wet > 0.4
Pendulum, BS EN 16165 Annex C	PTV >= 36 (low slip potential)

Reference: slip rating scales

DIN EN 16165 Annex B	Class
< 6 deg	Not classifiable
6 to 10 deg	R9
10 to 19 deg	R10
19 to 27 deg	R11
27 to 35 deg	R12
> 35 deg	R13

DIN EN 16165 Annex A	Class
< 12 deg	Not classifiable
>= 12 deg	A
>= 18 deg	B
>= 24 deg	C

DCOF (ANSI A326.3) use	Minimum
Interior dry / wet	>= 0.42
Interior wet plus	>= 0.50
Exterior wet / oils and greases	>= 0.55

Pendulum (PTV)	Slip potential
0-24	High
25-35	Moderate
36 and above	Low

Slip-resistance values are indicative and not binding. Confirm any specific requirement before ordering and always before installation.